

选型参数表
Selection Table

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机型号 Type Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _s	机型号 Type Type	极数 Pole p
1.5kW						1.5kW					
2.5	5100	560	1.42	FA 107R77	4	15	871	90.59	0.88		
2.9	4453	489	1.62	FAF107R77	4	18	750	77.97	1.03		
3.3	3889	427	1.86	F 107R77	4	21	636	66.13	1.21		
3.8	3369	370	2.1	FF 107R77	4	23	574	59.70	1.34		
						27	505	52.53	1.53	FA 67	4
2.6	4863	534	0.83	FA 97R57	4	28	477	49.60	1.62	FAF67	4
3.0	4298	472	0.94	FAF97R57	4	33	406	42.23	1.90	F 67	4
3.4	3734	410	1.08	F 97R57	4	36	369	38.38	1.99	FF 67	4
3.8	3342	367	1.21	FF 97R57	4	39	349	36.30	2.2		
						44	309	32.08	2.5		
4.1	3142	345	0.90	FA 87R57	4	51	264	27.41	2.9		
4.7	2732	300	1.03	FAF87R57	4	56	242	25.13	3.2		
						24	568	59.10	0.99		
2.7	4981	255.25	1.48	FA 107	8	28	483	50.22	1.17	FA 57	4
3.2	4197	215.04	1.76	FAF107	8	31	431	44.84	1.31	FAF57	4
3.5	3890	199.31	1.89	F 107	8	37	368	38.30	1.53	F 57	4
3.9	3486	178.64	2.1	FF 107	8	39	345	35.87	1.63	FF 57	4
						46	291	30.22	1.94		
3.6	3736	255.25	2.0	FA 107	6	33	409	42.55	0.92		
4.3	3147	215.04	2.3	FAF107	6	39	350	36.34	1.08		
4.6	2917	199.31	2.5	F 107	6	41	327	34.04	1.15		
5.2	2615	178.64	2.8	FF 107	6	46	295	30.64	1.28		
						48	280	29.11	1.34	FA 47	4
3.3	4049	276.64	1.00	FA 97	6	49	276	28.67	1.36	FAF47	4
3.6	3729	254.79	1.08	FAF97	6	55	246	25.54	1.53	F 47	4
4.1	3313	226.34	1.22	F 97	6	65	208	21.66	1.80	FF 47	4
4.9	2759	188.50	1.47	FF 97	6	72	188	19.56	2.0		
5.2	2574	178.83	1.57			81	166	17.21	2.3		
						86	156	16.25	2.4		
5.1	2661	276.64	1.52	FA 97	4	101	133	13.83	2.8		
5.5	2451	254.79	1.65	FAF97	4						
6.2	2177	226.34	1.86	F 97	4						
7.4	1813	188.50	2.2	FF 97	4						
8.0	1691	178.83	2.4								
5.2	2615	271.92	1.08			68	198	20.57	0.95		
5.5	2452	254.93	1.15			73	185	19.27	1.01		
6.1	2198	228.57	1.28			82	164	17.03	1.15		
7.1	1893	196.85	1.49	FA 87	4	98	138	14.33	1.36		
7.8	1721	178.95	1.63	FAF87	4	109	124	12.87	1.52		
8.8	1535	159.61	1.84	F 87	4	126	107	11.08	1.68	FA 37	4
10	1290	134.16	2.2	FF 87	4	134	100	10.42	1.74	FAF37	4
13	1053	109.49	2.7			156	86	8.97	1.91	F 37	4
14	942	97.89	3.0			175	77	8.01	2.1	FF 37	4
						206	66	6.81	2.0		
						229	59	6.11	2.2		
						266	51	5.27	2.3		
						283	48	4.95	2.4		
						329	41	4.26	2.5		
						367	37	3.81	2.7		
8.4	1601	166.47	0.88			2.2kW					
9.8	1368	142.27	1.03			1.00	18699	1420	0.90		
11	1254	130.42	1.12			1.09	17224	1308	0.98		
12	1101	114.45	1.28			1.21	15394	1169	1.10		
13	1043	108.46	1.35			1.49	12549	953	1.35		
15	913	94.93	1.54			1.68	11127	845	1.52	FA 157R97	4
16	823	85.52	1.71	FA 77	4	1.86	10061	764	1.68	FAF157R97	4
19	722	75.02	1.95	FAF77	4	2.1	8954	680	1.89	F 157R97	4
19	695	72.29	2.0	F 77	4	2.5	7585	576	2.2	FF 157R97	4
21	637	66.28	2.2	FF 77	4	3.2	5873	446	2.9		
24	559	58.16	2.5			4.7	3964	301	4.3		
25	530	55.12	2.7			5.2	3582	272	4.7		
29	464	48.24	3.0			6.1	3042	231	5.6		
32	418	43.46	3.0			7.2	2581	196	6.6		
37	367	38.12	3.4								
38	352	36.52	3.8			1.31	14288	1085	0.79	FA 127R77	4
44	303	31.45	4.3			1.52	12339	937	0.91	FAF127R77	4
						1.72	10890	827	1.04	F 127R77	4
						1.94	9652	733	1.17	FF 127R77	4

F

选型参数表
Selection Table

输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机型号 Type Type	极数 Pole p	输出转速 Output speed r/min	输出扭矩 Output torque Nm	传动比 Ratio i	使用系数 Service factor f _B	机型号 Type Type	极数 Pole p
2.2kW						2.2kW					
2.22	8428	640	1.34	FA 127R77	4	26	767	55.12	1.84		
2.62	7137	542	1.58	FAF127R77	4	29	671	48.24	2.1	FA 77	4
2.90	6439	489	1.75	F 127R77	4	33	604	43.46	2.1	FAF77	4
3.36	5570	428	2.0	FF 127R77	4	39	509	36.52	2.3	F 77	4
						45	438	31.45	3.0	FF 77	4
2.3	8256	627	0.89			49	400	28.59	3.4		
2.5	7374	560	1.00	FA 107R77	4	56	355	25.50	4.0		
2.9	6439	489	1.14	FAF107R77	4						
3.3	5623	427	1.31	F 107R77	4	24	830	59.70	0.93		
3.9	4767	362	1.55	FF 107R77	4	27	731	52.53	1.06		
4.3	4306	327	1.71			29	690	49.60	1.12		
						34	587	42.23	1.31		
3.9	4833	367	0.84	FA 97R57	4	37	534	38.38	1.37	FA 67	4
4.9	3792	288	1.07	FAF97R57	4	43	462	33.24	1.50	FAF67	4
5.7	3253	247	1.24	F 97R57	4	44	446	32.08	1.73	F 67	4
				FF 97R57	4	52	381	27.41	2.0	FF 67	4
						57	350	25.13	2.2		
2.8	7100	255.25	1.02	FA 107	8	64	307	22.05	2.5		
3.3	5982	215.04	1.21	FAF107	8	68	291	20.90	2.7		
3.6	5544	199.31	1.30	F 107	8	78	254	18.29	3.0		
4.0	4969	178.64	1.45	FF 107	8						
3.7	5363	255.25	1.35	FA 107	6	32	624	44.84	0.90		
4.4	4518	215.04	1.60	FAF107	6	37	533	38.30	1.06		
4.7	4188	199.31	1.72	F 107	6	40	499	35.87	1.13	FA 57	4
5.3	3753	178.64	1.92	FF 107	6	47	420	30.22	1.32	FAF57	4
						57	347	24.96	1.56	F 57	4
						67	294	21.17	1.92	FF 57	4
5.6	3550	255.25	2.0	FA 107	4	74	266	19.11	2.1		
6.6	2991	215.04	2.4	FAF107	4	84	234	16.81	2.4		
7.1	2772	199.31	2.6	F 107	4	89	221	15.88	2.6		
7.9	2485	178.64	2.9	FF 107	4						
4.2	4755	226.34	0.85	FA 97	6	56	355	25.54	1.06		
5.0	3960	188.50	1.02	FAF97	6	66	301	21.66	1.25		
5.3	3694	175.83	1.09	F 97	6	73	272	19.56	1.38	FA 47	4
6.0	3302	157.16	1.22	FF 97	6	83	239	17.21	1.57	FAF47	4
						87	226	16.25	1.66	F 47	4
						103	192	13.83	1.95	FF 47	4
5.1	3848	276.64	1.05			113	175	12.57	2.2		
5.6	3544	254.79	1.14			130	151	10.89	2.5		
6.3	3148	226.34	1.28	FA 97	4	156	126	9.08	2.5		
7.5	2622	188.50	1.54	FAF97	4						
8.1	2445	175.83	1.65	F 97	4						
9.0	2186	157.16	1.85	FF 97	4						
10	1968	141.47	2.1			99	199	14.33	0.94		
11	1782	128.12	2.3			110	179	12.87	1.05		
						128	154	11.08	1.16		
7.2	2738	196.85	1.03			136	145	10.42	1.20		
7.9	2489	178.95	1.13			158	125	8.97	1.32	FA 37	4
8.9	2220	159.61	1.27			177	111	8.01	1.39	FAF37	4
11	1866	134.16	1.51			209	95	6.81	1.43	F 37	4
12	1715	123.29	1.64	FA 87	4	232	85	6.11	1.49	FF 37	4
13	1523	109.49	1.85	FAF87	4	269	73	5.27	1.60		
15	1361	97.89	2.1	F 87	4	287	69	4.95	1.64		
16	1224	88.01	2.3	FF 87	4	333	59	4.26	1.75		
19	1062	76.39	2.7			373	53	3.81	1.86		
21	951	68.40	3.0								
25	789	56.75	3.6								
28	699	50.29	4.0								
31	629	45.22	4.2								
12	1592	114.45	0.89			3kW					
13	1508	108.46	0.93	FA 77	4	1.2	20991	1169	0.81		
15	1320	94.93	1.07	FAF77	4	1.5	17113	953	0.99		
17	1189	85.52	1.19	F 77	4	1.7	15173	845	1.12	FA 157R97	4
19	1043	75.02	1.35	FF 77	4	1.9	13719	764	1.23	FAF157R97	4
21	922	66.28	1.53			2.1	12211	680	1.39	F 157R97	4
24	809	58.16	1.74			2.5	10343	576	1.64	FF 157R97	4
						3.2	8009	446	2.1		
						4.7	5405	304	3.1		
						5.2	4884	272	3.5		
						6.1	4148	231	4.1		
						7.2	3520	196	4.8		

F